

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1-5. Cancelled.

6. (Currently Amended) A heater system comprising:

a substrate disposed proximate a part to be heated;

a layered heater disposed proximate the substrate, the layered heater comprising:

at least one dielectric layer;

at least one resistive layer disposed on the dielectric layer, the resistive layer having sufficient temperature coefficient of resistance characteristics such that the resistive layer is a heater element and a temperature sensor; ~~[[and]]~~

two electrical lead wires connected to the resistive layer; and

a two-wire controller connected to the resistive layer through the two electrical lead wires, wherein the two-wire controller determines temperature of the layered heater using the resistance of the resistive layer and controls heater temperature accordingly through the two electrical lead wires, wherein the heater system provides heat to the part to be heated.

7. (Original) The heater system according to Claim 6, wherein the two-wire controller comprises a DC bias control for calculation of the resistance of the resistive layer.

8. (Original) The heater system according to Claim 6, wherein the two-wire controller comprises an AC bias control for calculation of the resistance of the resistive layer.

9. (Original) The heater system according to Claim 6, wherein the two-wire controller comprises high conduction angle firing.

10. (Original) The heater system according to Claim 6, wherein the two-wire controller comprises a shunt resistor for calculation of the resistance of the resistive layer.

11. (Original) The heater system according to Claim 6, wherein the two-wire controller further comprises a microprocessor.

12. (Withdrawn) The heater system according to Claim 6, wherein the resistive layer defines a pattern selected from the group consisting of spiral, rectangular, and circular.

13. (Original) The heater system according to Claim 6, wherein the two-wire controller further comprises firmware.

14. Cancelled.

15. (Withdrawn) A hot runner nozzle heater system comprising:  
at least one hot runner nozzle;  
a substrate disposed proximate the hot runner nozzle;  
a dielectric layer disposed on the substrate;

a resistive layer disposed on the dielectric layer, the resistive layer having sufficient temperature coefficient of resistance characteristics such that the resistive layer is a heater element and a temperature sensor;

a protective layer disposed over the resistive layer; and

a two-wire controller connected to the resistive layer, wherein the two-wire controller determines temperature of the heater system using the resistance of the resistive layer and controls heater system temperature accordingly.

16. (Withdrawn) A hot runner nozzle heater system comprising:

at least one hot runner nozzle; and

at least one resistive layer disposed proximate the runner nozzle, the resistive layer having sufficient temperature coefficient of resistance characteristics such that the resistive layer is a heater element and a temperature sensor; and

a two-wire controller connected to the resistive layer, wherein the two-wire controller determines temperature of the heater system using the resistance of the resistive layer and controls heater system temperature accordingly.

17. (Withdrawn) A heater system for use with an existing temperature controller having at least one temperature sensor input and a power output, the improvement comprising:

at least one layered heater, the layered heater comprising at least one resistive layer, the resistive layer having sufficient temperature coefficient of resistance

characteristics such that the resistive layer is a heater element and a temperature sensor; and

at least one two-wire module connected to the layered heater and to the temperature controller,

wherein the two-wire module determines temperature of the layered heater using the resistance of the resistive layer and transmits the temperature of the layered heater to the temperature controller input, and the temperature controller transmits the power output to the two-wire module.

18. (Withdrawn) A heater system comprising:

a layered heater comprising at least one resistive layer, the resistive layer having sufficient temperature coefficient of resistance characteristics such that the resistive layer is a heater element and a temperature sensor;

an electrical lead connected to the resistive layer;

a controller connected to the resistive layer through the electrical lead, wherein the controller determines temperature of the layered heater using the resistance of the resistive layer and controls heater temperature accordingly;

a common return device connected to the layered heater; and

a power source connected to the controller,

wherein the common return device provides an electrical return to the controller from the layered heater.

19. (Currently Amended) A method of operating a layered heater comprising the steps of:

placing a substrate proximate a part to be heated;

supplying power to the layered heater through ~~a set of~~ two electrical leads lead wires to a resistive layer of the layered heater;

transferring heat from the resistive layer, through a dielectric layer of the layered heater, and to the substrate; and

calculating the temperature of the resistive layer using a two-wire controller connected to the layered heater through the ~~set of~~ two electrical leads lead wires,

wherein the resistive layer is a heater element and a temperature sensor.

20. (Original) The method according to Claim 19, further comprising the step of resistance data calibration.

21. (Original) The method according to Claim 19, further comprising the step of lead wire calibration.

22. (Original) The method according to Claim 19, further comprising the step of temperature calibration.

23. (Original) The method according to Claim 19, further comprising the step of TCR calibration.

24. (Withdrawn) A method of operating a layered heater in conjunction with a hot runner nozzle system comprising the steps of:

supplying power to the layered heater through a set of electrical leads to a resistive layer of the layered heater; and

calculating the temperature of the resistive layer using a two-wire controller connected to the layered heater through the set of electrical leads,

wherein the resistive layer is a heater element and a temperature sensor.

25. (New) The heater system according to Claim 6, wherein the layered heater is selected from a group consisting of thick film, thin film, thermal spray, and sol-gel.